







LORING[™] S35 Kestrel[™]

Automated 35 kg Roaster

INCLUDES

- Touchscreen interface
- Green bean vacuum lift
- Automation software with auto-charge and discharge of beans
- High speed cooling tray with paddle stirring
- Green bean cart with scale
- 7-35 kg batch capacity

OPTIONAL

Destoner

ROASTER SPECIFICATIONS	
Maximum Batch Size	77 lb (35 kg)
Minimum Batch Size	15.4 lb (7 kg)
Nominal Electrical Power	3.8 kW
Peak Electrical Power	7.2 kW
Maximum BTU Rating	310,000 BTU/h (78,200 kcal/h)
Stack Temp Continuous	1,450°F (788°C)
Stack Temp Intermittent	1,550°F (844°C)
Stack Flow Continuous	120 scfm (205 dsm³/h)
Stack Max Flow (Peak Air Cool)	450 dscfm (765 dsm³/h)
Stack Duct Diameter (Minimum)*	8 in (203 mm)
Cooler Vent Max Flow	1,200 scfm (2,035 sm³/h)
Cooler Duct Diameter [*]	8 in (203 mm)
Water Supply	1 GPM (4 liter/min)
Water Pressure	50 psi (345 kPa)
Natural Gas Pressure	4-7 in WC (1.0-1.7 kPa)
Propane Gas Pressure	11-13 in WC (2.7-3.2 kPa)
Weight	1,900 lb (862 kg)

*Larger stack diameters may be required based upon stack geometry

SUPERIOR IS OUR STANDARD.

Engineered for a roasting experience like no other, every Loring machine gives you unmatched quality, unheard-of efficiency, and unparalleled control.



UNMATCHED QUALITY.

- Designed and made in U.S.A.
- Constructed by skilled craftsmen.
- Stainless steel construction.
- ISO 9001:2015 certified.

UNPARALLELED CONTROL.

- Touch screen and PID provide operation of burner and fan speeds.
- Profiles can be saved and repeated consistently.
- Fully automated roasting process.

UNHEARD-OF EFFICIENCY.

- Single burner roasts beans and incinerates smoke.
- High-speed cooling tray reduces cooling time while protecting beans.
- Up to 80% fuel-savings and reduction of greenhouse gases in every roast, compared to conventional roasters.

Contact Us

Loring Smart Roast, Inc.

3200 Dutton Avenue, Suite 413 Santa Rosa, CA 95407 +1 707 526 7215 sales@loring.com

North America, Latin America

ORING

ZENDEUS San Francisco, California + 1 415 374 9097 duncan.elcombe@zendeus.com

Australia, New Zealand

CT ROASTING SOLUTIONS Adelaide, South Australia +61 400 250 598 lachlan@ctroastingsolutions.com.au

Southern Asia

UCC K2 COMPANY LTD. Bangkok, Thailand +66 2276 5170 sales@ucck2.co.th

China (PRC), Hong Kong

SHANGHAI FORTUNECAFFE CO. Shanghai, China +86 21 6249 9786 sales@fortunecaffe.com

Japan, Taiwan

DCS CO., LTD Osaka, Japan +81 798 35 2980 info@dcservice.co.jp

Korea

M.I. COFFEE CORPORATION Seoul, South Korea + 82 592 0167 mi@micoffee.co.kr

Europe, UK, Middle East

THE COFFEE ROASTING COMPANY APS Copenhagen, Denmark +45 3023 8775 jht@thefactorycoffee.eu

SCHEDULE A DEMO OR REQUEST A QUOTE AT LORING.COM

© 2022 Loring Smart Roast, Inc. The following are trademarks of Loring Smart Roast, Inc.: Loring, The Smarter Way to Roast, S7 Nighthawk, S15 Falcon, S35 Kestrel, S70 Peregrine and the flame symbol. 1002696 Rev. F